

Options

Roof and Protective Net



Grass Collector



Scraper



■ Specifications

Model		SR525	
Dimensions			
Length		(mm)	2700 (2970)
Width	Mowing	(mm)	2900
	Transport	(mm)	2240
Height		(mm)	2040 (include ROPS)
Wheel Base		(mm)	1510
Tread Width	Front	(mm)	1730
	Rear	(mm)	1045
Ground Clearance		(mm)	160
Tires	Front		24×13.00—12 4PR
	Rear		20×8.00—10 4PR
Weight		(kg)	1300
Engine			
Model		Shibaura N843L	
Type		Water-cooled, 4 cycle, diesel	
Cylinders		3	
Displacement		(cc)	1662
Horsepower		[kW (hp)/rpm]	27.9 (38)/2850
Fuel Tank Capacity		(ℓ)	41
Battery		75D26L	
Transmission			
Drive		Hydrostatic Transmission, 2 range High/Low. Automatic Four-Wheel Drive or Permanent Four-Wheel Drive	
Brake		Wet Disc	
Steering		Hydraulic Power Steering	
Travelling Range	Forward	2	
	Reverse	2	
Travelling Speed	Forward	(km/h)	L : 0~10.0 H : 0~17.1
	Reverse	(km/h)	L : 0~7.0 H : 0~11.9
Reel Mower			
Total width of cut		(mm)	2500
Reel diameter		(mm)	∅178
Number of reel		9 Blade-Standard (7/11 Blade-Optional)	
Height of cut		(mm)	7~32
Mowing Rate		(a/h)	183 (Mowing Speed 9km/h, Efficiency 0.8)

Important information ● Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

※We reserve the right to discontinue models or change specifications without notice.

SHIBAURA

SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 T. (0031) 026 326 9999
 F. (0031) 026 326 9990
 E. info@shibaura.com
 www.shibaura.com

Catalog No. 2674 Printed in Japan

Lightweight 5 fairway mower

SR525

SHIBAURA

Lightweight, Compact and High-performance
 Fairway Mower



SHIBAURA

Lightweight and compact styling, excellent operator comfort and superb cutting performance. Low centre of gravity ensures stable performance over undulating ground, mechanical 4WD ensures excellent climbing capabilities without loss of power.

SR525

Width of cut : 2500mm

Safety Features

- Mower revolution stops when lifting up reel mower
- Engine stops when operator leaves seat



Operator Comfort

Adjustable seat suspension, reclining seat and a tilt steering wheel ensure operator comfort.

Excellent visibility to reel mower



Tilting Steering Wheel

Adjustable Seat Suspension



Reclining Seat

Sliding Seat

Maintenance made easy - Reduced Service Time
Access to all major components is made simple with tilting operator seat / platform and full bonnet opening. Radiator can be cleaned easy by opening the front screen and retractable shutter.



Low Emission Shibaura Diesel Engine
Equipped with Shibaura diesel engine, complying with Tier 2 U.S. emission regulation.




Easy Operation
Ergonomically designed controls for ease of use.



Divertor Valve
All cutting units are fitted with diverter valves enabling the back lap of individual units.



Cutting Unit Adjustment
Centre cutting units can be easily rotated and moved sideways to adjust the roller bracket position, cutting height and grass discharge cover.



Easy adjustment of cutting height

